

Product Specifications - 4" & 6" Round LED Retrofit



Technical Specifications

- Housing: spun aluminum with white powder coat finish
- Trim ring: integrated spun aluminum white powder coat finish
- Gasket: close cell Neoprene foam gasket
- Lens: 0.125" white translucent acrylic
- Isolated driver for improved thermal management
- Color temperature: 3000K (WW, 4000K (NW), 5000K (DW)
- Working voltage: 120v AC
- Dimmable: Yes
- LED: EPISTAR chip (COB) and driver—36,000 hour design life
- Power factor: 90% +
- Suitable for damp locations
- Maximum ambient 4°C (104°F)
- 5-year warranty
- UL-listed / Energy Star-rated



Product Name	Chip	Wattage	Voltage	Lumens	Color Temp
RDL4-41K-WP	Epistar COB	12W	120V AC	750 NW	4100K
RDL4-27K-WP	Epistar COB	12W	120V AC	650 WW	2700K
RDL4-30K-WP	Epistar COB	12W	120V AC	700 WW	3000K
RDL4-50K-WP	Epistar COB	12W	120V AC	800 DW	5000K
RDL6-27K-WP	Epistar COB	19W	120V AC	1200 WW	2700K
RDL6-30K-WP	Epistar COB	19W	120V AC	1250 WW	3000K
RDL6-41K-WP	Epistar COB	19W	120V AC	1300 NW	4100K
RDL6-50K-WP	Epistar COB	19W	120V AC	1350 DL	5000K