

LED TRIMS ADJUSTABLE DOWNLIGHT



Technical Specifications

Housing: spun aluminum with white powder coat finish
 Trim ring: integrated spun aluminum white powder coat finish
 Gasket: close cell Neoprene foam gasket
 Lens: 0.125" white translucent acrylic
 Isolated driver for improved thermal management
 CRI: 90
 Working voltage: 120V AC
 Dimmable
 LED: EPISTAR chip (COB) and driver—36,000 hour design life
 Power factor: 90% +
 Suitable for damp locations
 Maximum ambient 4°C (104°F)
 5-year warranty
 UL-listed
 Energy Star rated (2700K and 3000K)
 Adjustable bracket can fit 5" and 6" housings
 Quick connect connector

SKU No. - 4inch downlights

Product Name	Chip	Wattage	Voltage	Lumens	Color Temp
RDL4-ADJ-30K	Epistar COB	10W	120V AC	650	WW 3000K
RDL4-ADJ-41K	Epistar COB	10W	120V AC	650	NW 4100K

SKU No. - 6inch downlights

Product Name	Chip	Wattage	Voltage	Lumens	Color Temp
RDL6-ADJ-30K	Epistar COB	12W	120V AC	900	WW 3000K
RDL6-ADJ-41K	Epistar COB	12W	120V AC	900	NW 4100K

